

LP-WU6600 DLP Laser Projector

HITACHI
Inspire the Next

Accessories and Lenses

Supplied Accessories	Remote control, power cord, AA batteries x 2, user's manual cd, user's manual, RGB cable, wire remote cable, 3D sync cable x 2, mount cap, EAC document
Optional Lenses	SD-63 Standard, ML-64 Long Throw
Replacement Parts	
Remote Control	HL03171

Projection Throw Chart

Screen Size 16:10		Throw Distance	
Diagonal	Width	Min	Max
36.1	31	48	60
50	42	66	82
80	68	105	132
100	85	131	164
120	102	157	197
150	127	196	246
200	170	262	328
211	179	276	346

Throw Ratio: 1.5 - 1.9 : 1 (distance : width)
Screen size and throw distance are measured in inches with standard lens SD-63.

Projection Lens Chart

Lens	Inches	Meters
SD-63	131 - 164	3.3 - 4.2
ML-64	161 - 243	4.1 - 6.2

Projection distances measured in inches and meters with standard lens and optional lenses when projecting onto a 100" diagonal screen.

Specifications

Display	Projection Technology	Single Chip DLP
	Resolution	WUXGA 1920 x 1200
	Brightness	6,000 ANSI lumens
	Colors	1.07 billion colors
	Aspect Ratio	Native 16:10 and 4:3 / 16:9 compatible
	Contrast Ratio	20,000 : 1 (Dynamic black on)
Operation	Throw Ratio (distance : width)	Specifications will vary depending on which lens is used with the projector
	Focus Distance	59" - 275" (with SD-63 lens)
	Display Size	36" - 211" (with SD-63 lens)
	Lens	Specifications will vary depending on which lens is used with the projector
	Expected Light Source Life*	Approximately 20,000 hours
	Speaker Output	12W
Compatibility	Keystone	H: +/-25° and V: +/-30°
	Computer	VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, WSXGA+, UXGA, WUXGA, MAC16"
	H-Sync	15 kHz - 91 kHz
	V-Sync	24 Hz - 85 Hz
	Composite Video	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	Component Video	480i, 480p, 576i, 720p, 1080i, 1080p
Connectors	HDMI	480p, 720p, 1080i, 1080p, Computer signal TMDS clock 27 MHz - 162 MHz
	Digital Input	HDBaseT x 1, HDMI x 1, HDMI/MHL x 1, DVI-D x 1
	DVI-D	DVI-D connector x 1
	Computer Input 1	15-pin mini D-sub x 1 (shared with analog component video input)
	Computer Input 2	5 BNC connector x 1 (shared with component video input)
	Computer Monitor Output	15-pin mini D-sub x 1
	Video Input	
	Composite Video	RJ-45 jack x 1
	Component Video	5 BNC x 1 (shared with analog computer input), 15-pin mini D-sub x 1 (shared with analog computer input)
	Audio Input	3.5mm stereo mini jack x 1, RCA jack (L/R) x 1
	Audio Output	RCA jack (L/R) x 1
	Network LAN Wired	RJ-45 jack x 1
	Wired Remote	3.5 mm Stereo mini jack x 1 (In and Out)
	HDBaseT	RJ-45 jack x 1
	Control Terminals	9-pin D-sub x 1 for RS-232 control in (Serial, Cross) 9-pin D-sub x 1 for RS-232 control out (Serial, Cross) HDBaseT
Trigger	3.5 mm stereo mini jack	
3D Sync	VESA 3-pin x 1 (In and Out)	
Ratings & Warranty	Power Supply	AC100-130V / AC200-240V, 50/60HZ
	Power Consumption	650W
	Operating Temperature	32°F - 95°F (0°C-35°C) Normal mode 32°F - 104° (0°C-40°C) Eco mode
	Dimensions (W x D x H)	18.5" x 20.5" x 8.7"
	Weight	Approximately 54.5 lbs.
	Approvals	UL 60950-1 / cUL FCC Part 15 subpart B class A
Warranty	3 year limited parts and labor Extended Service Contract available (additional cost)	

* Actual light source life will vary by individual light source based on environmental conditions, selected operating mode, user settings and usage. Hours of average light source life specified are not guaranteed and do not constitute part of the product or light source warranty. Light source brightness decreases over time.



HI0551-07/17
All specifications subject to change without notice.
DLP and the DLP logo are registered trademarks of Texas Instruments. Crestron® and Crestron RoomView® are registered trademarks of Crestron Electronics, Inc. in the United States and other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance.
©2017 Hitachi America, Ltd. All Rights Reserved.



Hitachi America, Ltd.

Toll Free: 1.800.HITACHI • Email: dmd.info@hal.hitachi.com
Web: hitachi-america.us/projectors

